

..... اسم المدرس: اسم الطالب:
 Student . #: _____ Section #: _____ Seat #: _____

Q1) Given the following definition of a **slist**, use the functions whose prototype appear in the public section (if needed) to answer questions **A-C** :

```
class slist
{
private:
    node * head; //pointer that points to the first node in a list
public:
    int delete_head(); //deletes the first node
    void delete_node(int el);
};
```

- A. Write a proper destructor for the above class.

```
slist::~slist() →1 Mark
{
    while(head!=NULL) →1 Mark
        delete_head(); →1 Mark
}
```

- B. Add a definition of function **delete_tail** to a class **slist** that will delete the last node from the above defined linked list and return the value of the deleted node.

```
int slist::delete_tail() →1 Mark
{
    int el;
    if(head->next == NULL) →1 Mark
    {
        el = head ->info;
        delete head; →1 Mark
        head = NULL;
    }
    else
    {
        node * tmp=head; →1 Mark
        while(tmp->next->next != NULL) →1 Mark
            tmp=tmp->next;
        el = tmp->next->info;
        delete tmp->next; →1 Mark
        tmp->next=NULL;
    }
    return el;
}
```

Instructor:Nabeel ALassaf

- C. Write a definition of a function delete_odds that will delete all nodes that contain odd integers.

```
void slist::delete_odds()
{
    node *tmp1=head,*tmp2=head->next;      ➔1 Mark
    while (tmp1!=NULL)           ➔1 Mark
    {
        if ((tmp1->info % 2) != 0)   ➔1 Mark
        {
            cout<<"deleting "<<tmp1->info;
            delete_node(tmp1->info); ➔1 Mark
        }
        if(tmp2!= NULL)
        {
            tmp1=tmp2; ➔1 Mark
            tmp2=tmp2->next;
        }
        else
            tmp1=tmp2;
    }
}
```

- Q2) Given the following definition of a **dlist**, use the functions whose prototype appear in the public section (if needed) to answer questions A,B :

```
template <class T>
class dlist
{
private:
    node<T> * current; // pointer that points to any node in a list
public:
    void add_head(T el);           // adds element at begin
    void add_tail (T el);         // adds element at end
    void add_at_pos(int pos,T el); //adds element at position
};
```

- A. Add a definition of a function print_back to class dlist that will print all elements of a list backwards.

Template <class T> ➔1 Mark
Void dlist<T>::print_back()
{
While(current->next!=NULL) ➔1 Mark
current=current->next;

While(current!=NULL) ➔1 Mark
{
Cout<< current->info; ➔1 Mark
current=current->prev; ➔1 Mark
}
}

Instructor:Nabeel ALassaf

- B. Add a definition of a function add_sorted to a dllist that will add an element in a correct position into a liked list that contains elements sorted increasingly.

Template <class T>

```
Void dllist<T>::add_sorted(T el)
{
    for ( ;current->prev!=NULL ;current=current->prev);→1 Mark
    int p=0; →1 Mark
    while(current!=NULL && current->info<el) →2 Mark
    {
        current=current->next;
        p++; →1 Mark
    }
    Add_at_pos(p,el); →1 Mark
}
```

- Q3)** Count number of assignments in the following code, then find its complexity.

```
for(i=1 ; i<=m ; i+=2)
    for(j=i-2 ; j<=i+2 ; j++)
        sum+=a[j]
```

number of assignments is:

$$\begin{aligned}
 &= 1 + \overbrace{m/2}^1 + \overbrace{m/2}^{2 \cdot m/2} + \overbrace{5}^{* 5} \quad \rightarrow 3 \text{ Mark} \\
 &= 1 + m + 5m \\
 &= 1 + 6m \\
 &\rightarrow O(m)
 \end{aligned}$$

- Q4)** Find complexity of the following code.

```
for( k=0 , j=1 ; j<=B ; j*=2)
    k++;
    for ( j=1; j<=B ; j++)
        s++;
```

$$\begin{aligned}
 &= 2 + 2 * \log B + 1 + 2B \\
 &= 3 + 2B + 2 * \log B \\
 &\rightarrow O(B) \rightarrow 2 \text{ Mark}
 \end{aligned}$$